

# Offer

Ref.: Installation :ITEM 6 Offer N° : of

INSTALLATION	GIVEN	SUPPOSED
Type of roping	1 : 1	
Car speed [m/s]	1,00	
Duty load [Kg]		
Car weight [Kg]		
Ropes n° x diameter [mm]	6 x 11	
Angle groove [°]	V / 35	
Angle undercut groove [°]	97	
Car travel [m]		
Ropes weight [Kg]		
Counterweight [Kg]		
Counterweight [%]		
Comp. chains weight [Kg]		
Comp. chains weight [%]		
Out of balance load [Kg]		
Static load [kg]		
Shaft efficiency [%]		80
Machine	Above	
Divertors on bearings nr		
Divertors on bushing nr		
Minimum alfa angle [°]		
Regulation	4/00VVVF	
Tropicalization	NO	
Voltage [V]	380	
Ropes tensile strength [kg]		
Type of ropes	Fiber core	
<b>Material not included in price</b>		
Flat / High frame		
Distance between ropes [mm]		0
Vibration dampers	NO	
Divertors Ø [mm]		
Divertor protection		
Extended shaft	NO	
Centre gear-sheave [mm]		
Centre gear-bearing [mm]		
Static load [Kg]		

GEAR / MOTOR		Price-List €
<b>GEAR</b>		
Quantity n°	TORO	
Traction sheave position	to be defined	
Ratio	1/39	
Traction sheave diameter [mm]	520	
Ropes n° x diameter [mm]	6 x 11	
Angle groove [°]	V / 35	
Angle undercut groove [°]	97	
Pitch of grooves [mm]	18	
Drum Brake voltage DC [V]	220	
Flywheel	400-32P	
MAX. static load [kg]	4200	
MAX. out of balance load [kg]	597	
Traction sheave speed [m/s]	1,00	
<b>MOTOR</b>		
Frame size	SASSI	
Poles / Regulation	240142A	
Power [kW syncr.]	4/00VVVF	
Voltage [V]	11	
Rated frequency [Hz]	380	
Rated current [A]	50	
Acceleration current [A]	27,50	
Thermistors	55,00	
Sts./h. - ED%	3	
Power [kW asyncr.]	240 40	
Adjusting frequency [Hz/RPM]	11	
Full load current [A]	51,99 / 1.559	
<b>ACCESSORIES</b>		
Ropes protection	Q.ty	
Packing	1	

Payment

Goods delivered

Packing

Offer valid through

  
Delivery time

	Net €	Price-List €
Unit price		
Total price		