

**ACCESSORIES**  
**Suspension devices**  
for FL and FM cables



Figure 1:  
Suspension device LZ 1006



Figure 2:  
Suspension device LZ 1009



Figure 3:  
Suspension device LZ 1010

## PRODUCT INFORMATION

### APPLICATION

Suspension devices for Datwyler FL and FM elevator travelling cables.


The cable width, number of cables (cable combinations) to be mounted and travelling height determine the selection of the correct cable suspension device(s).

To this end, please note the maximum clamping thickness of the individual suspension parts.

### MATERIAL

Nylon PA6	LZ 1006 / LZ 1009	grey
Aluminium	LZ 1010	blue anodised

### DIMENSIONS



LZ 1006

A = 100 mm  
B = 65 mm  
C = 47 mm  
D = 55 mm  
E = 155 mm  
F = 43 mm  
G = 73 mm  
H = Ø 13.9 mm  
I = Ø 6.45 mm  
T = 5.2 mm



LZ 1009

A = 120 mm  
B = 92 mm  
C = 51.5 mm  
D = 79 mm  
E = 272 mm  
F = 73 mm  
G = 40 mm  
H = Ø 13.9 mm  
I = Ø 6.45 mm  
T = 5.2 mm



LZ 1010

A = 140 mm  
B = 120 mm  
C = 50 mm  
D = 100 mm  
E = 322 mm  
F = 96 mm  
G = 60 mm  
H = Ø 15.0 mm  
I = Ø 8.0 mm  
T = 6.0 mm

Article no.	Type	Colour	Cable damping range maximum [mm]	Width of cable a [mm]	Screw holes	Figure
17981	LZ 1006	grey	3 - 12 mm	a 55 mm	3	1
17984	LZ 1009	grey	3 - 15 mm	a 56 - 79 mm	4	2
163354	LZ 1010	blue	3 - 22 mm	a 80 - 100 mm	4	3