

# BM Series

Type	Order Number	Traction Ratio	Load (kg)	Max. axle load (kg)	Elevator Speed (m/s)	Rated Speed (RPM)	Rated Torque (N.m)	Motor					Brake		Sheave					Weight (Kg)	
								Power (Kw)	Voltage (V)	Current (A)	Poles (P)	Frequency (Hz)	Voltage (V)	Brake Torque (N.m)	Diameter (mm)	Rope Dia. (mm)	Rope Qty.	$\beta$ angle (°)	$\gamma$ angle (°)		Groove Pitch (mm)
BM320	BE0211391031	2:1	630	3500	1	119	311	3.9	380	10.2	10	19.83	DC 207	2x800	φ 320	φ 8	4	97	35	12	320
	BE0211681731	2:1	630	3500	1.75	191	311	6.8	380	15.6	10	31.8	DC 207	2x800	φ 320	φ 8	4	97	35	12	320
	BE0211491039	2:1	800	3500	1	119	393	4.9	380	11.8	10	19.83	DC 207	2x800	φ 320	φ 8	5	97	35	12	320
	BE0211861739	2:1	800	3500	1.75	191	393	8.6	380	18.9	10	31.8	DC 207	2x800	φ 320	φ 8	5	97	35	12	320
BM360	BE0211601048	2:1	1000	3500	1	119	482	6	380	14.3	10	19.83	DC 207	2x800	φ 320	φ 8	6	97	35	12	330
	BE0211A71748	2:1	1000	3500	1.75	191	482	10.7	380	24	10	31.8	DC 207	2x800	φ 320	φ 8	6	97	35	12	330
BM390	BE0211701056	2:1	1150	3500	1	119	562	7	380	16.9	10	19.83	DC 207	2x800	φ 320	φ 8	8	97	35	12	340
	BE0211C31756	2:1	1150	3500	1.75	191	562	12.3	380	26	10	31.8	DC 207	2x800	φ 320	φ 8	8	97	35	12	340

Type	Order Number	A	B	C
BM320	BE0211391031	315	365	654
	BE0211681731	315	365	654
	BE0211491039	315	365	654
	BE0211861739	315	365	654
BM360	BE0211601048	355	405	694
	BE0211A71748	355	405	694
BM390	BE0211701056	385	435	724
	BE0211C31756	385	435	724

